

SPECIAL SCREWS AND ACCESSORIES → SAFETY SCREWS FOR RIM LOCKS

Safety Screws

FOR RIM LOCKS



Safety Screws

FOR RIM LOCKS


ISS injection safety screws for rim locks

When tightening the screw the resilient plastic material “peek” is slightly compressed.

This provides:

- Locking function against self-loosening of the screw
- Perfect adjustment function
- Sealing function

These functions remain unchanged, even if the screw is disassembled multiple times.



6 point star screw

| OBE No. | Thread | Total length | Shaft length | Head Ø |
|----------|--------|--------------|--------------|--------|
| 99-04609 | M1.4 | 3.5 | 2.8 | 2.0 |
| 99-04602 | M1.4 | 4.3 | 3.6 | 2.0 |



Minus screw

| OBE No. | Thread | Total length | Shaft length | Head Ø |
|----------|--------|--------------|--------------|--------|
| 99-01546 | M1.2 | 3.1 | 2.3 | 1.6 |
| 99-01548 | M1.2 | 3.6 | 2.8 | 1.6 |
| 99-01549 | M1.2 | 4.1 | 3.3 | 1.6 |
| 99-01550 | M1.2 | 4.5 | 3.7 | 1.6 |
| 99-01551 | M1.2 | 5.0 | 4.2 | 1.6 |
| 99-01538 | M1.4 | 2.6 | 1.8 | 1.8 |
| 99-01542 | M1.4 | 2.8 | 2.0 | 1.8 |
| 99-01541 | M1.4 | 3.1 | 2.3 | 1.8 |
| 99-01539 | M1.4 | 3.4 | 2.6 | 1.8 |
| 99-01543 | M1.4 | 3.5 | 2.7 | 1.8 |
| 99-01584 | M1.4 | 3.6 | 2.9 | 2.0 |
| 99-01537 | M1.4 | 3.9 | 3.1 | 1.8 |
| 99-01545 | M1.4 | 4.0 | 3.2 | 1.8 |
| 99-01585 | M1.4 | 4.0 | 3.2 | 2.0 |
| 99-01540 | M1.4 | 4.4 | 3.6 | 1.8 |
| 99-01547 | M1.4 | 5.0 | 4.2 | 1.8 |



Plus-minus screw

| OBE No. | Thread | Total length | Shaft length | Head Ø |
|----------|--------|--------------|--------------|--------|
| 99-01624 | M1.2 | 3.2 | 2.6 | 1.8 |
| 99-01627 | M1.2 | 4.4 | 3.8 | 1.8 |
| 99-01690 | M1.4 | 2.4 | 1.8 | 2.0 |
| 99-01610 | M1.4 | 2.7 | 2.1 | 2.0 |
| 99-01606 | M1.4 | 3.0 | 2.4 | 2.0 |
| 99-01644 | M1.4 | 3.2 | 2.6 | 1.8 |
| 99-01604 | M1.4 | 3.2 | 2.6 | 2.0 |
| 99-01609 | M1.4 | 3.4 | 2.8 | 2.0 |
| 99-01603 | M1.4 | 3.6 | 3.0 | 2.0 |
| 99-01601 | M1.4 | 3.8 | 3.2 | 2.0 |
| 99-01608 | M1.4 | 4.0 | 3.4 | 2.0 |
| 99-01602 | M1.4 | 4.2 | 3.6 | 2.0 |
| 99-01607 | M1.4 | 4.6 | 4.0 | 2.0 |
| 99-01605 | M1.4 | 5.0 | 4.4 | 2.0 |
| 99-01600 | M1.4 | 5.9 | 5.3 | 2.0 |



90% of the recycled plastic sprues are used for injection of new safety screws



OBE GmbH & Co. KG · Turnstr. 22 · 75228 Ispringen · Germany
Tel. +49 7231 802-0 · www.obe.de · info@obe.de